CIRCULAR

Sub :- Town Panchayats Administration - Construction of office building / Preparing estimate - Instruction Issued- regarding

Ref:- Connected files

The following points are to be taken into consideration while preparing the estimate for construction and reparing works of office building and construction of culvert.

- 1. The detailed specification are to be incorporated for each and every item in the estimate as per T.N.D.S.S for buildings.
- 2. For all R.C.C. works $1:1\frac{1}{2}:3$ Mix is to be used (Grade M 20) as per I.S. 456-2000.
- 3. The clear cover to the Reinforcemet is to be provided as per Indian Standard 456 2000. For coastal areas, additional cover is to be provided as per I.S. 456-2000.
- 4. Cement paint of two coats over one coat of white cement (primer) is advised for all cement plastered surfaces for better duraoility and aesthetic appearance.
- 5. Country wood door are suggested instead of mild steel door for elegant look. For bath rooms P.V.C. door are suggested for longer life and easy maintenance.
- 6. Aluminum windows are suggested for elegant look, due to lesser cost of maintenance and also to maintain the ecological balance.
- 7. Dadooing with ceramie tiles may be restricted to bathroom and toilet.
- 8. Painting of new walls using distemper is not advised.
- 9. The foundation for the office building may be suitably adopted as per the soil condition.
- 10. Data is to be attached with detailed estimate.

Sd/. K. GOPAL

Director

To

The Assistant Executive Engineer,

All Zones.